

ASCOM 30T

DESCRIPTION & APPLICATIONS

Premium quality surface coated calcium carbonate with good dispersion properties, manufactured from a high purity and white ground calcium carbonate.

Filler in the following industries:
Plasticized PVC pipes and masterbatch for mouldings.

Standard Packaging:
25 kg bag or
Jumbo bag

Physical Properties (typical)

Whiteness:	>97%
Brightness Ry (DIN 53163)	>95.5%
Density	2.7g/ml
Refractive Index	1.59
Mohs Hardness	3
pH (ISO 787/9)	9 Max.
Moisture	0.2% Max
Bulk Density	1.25 ± 0.05 gm/cm ³

Chemical Analysis (typical)

CaCO ₃	99.18%
CaO	55.91%
SiO ₂	0.09%
Al ₂ O ₃	0.04%
Fe ₂ O ₃	0.01%
MgO	0.05%
HCl Insoluble content	0.2% Max
L.O.I	43.64%

General Product Data (typical)

Retained on sieve 150μ	0.09% Max (coated)
D97	17 ± 1μm (uncoated)
D50	4.25 ± 0.25μm(uncoated)
< 2μm	30 ± 2% (uncoated)
Coating Level	0.75 - 0.85%

The data in the Technical Data Sheet represents average values which are valid and reliable but not legally binding. ACCM disclaims any liability arising from damages or consequential loss. This Technical Data Sheet renders all previous versions invalid. April 2024)

PARTICLE SIZE DISTRIBUTION (MALVERN)

